

Seat Belts for Forklift

Forklift Seat Belts - Described in the Regulation guidelines are the use of seatbelts and operator restraints on lift trucks. It states that the responsibility falls on the employers' to be able to make certain that each and every machine, piece of equipment and device is utilized rightly used according to the directions of the maker.

With regards to their maintenance, inspection, fabrication, use and design Rough Terrain forklifts need to satisfy the regulations of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile equipment with a Rollover Protective Structure, or ROPS for short, need to contain seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment includes seat belts required by law, the operator and subsequent passengers have to ensure they use the belts each time the vehicle is in motion or engaged in operation because this can cause the equipment to become unstable and thus, not safe.

When a seat belt or various driver restraint is needed on a forklift.

The seat belt requirements while operating a lift truck depend on various factors. Whether the forklift is equipped with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was actually manufactured all add to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, enclosure or system. An operator restraint device, enclosure or system is intended to aid the driver in reducing the possibility of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might consist of a seat belt, even if a seat belt is not essentially a part of such machine or system.